

BASIC USE

WindowSeal tape is a self sealing MicroSealant that creates a water tight seal between the window frame and virtually all structure subsurfaces or framing. Irregular or curved surfaces are easy because WindowSeal is extremely conformable. WindowSeal, if kept warm (room temperature+) prior to installation, can be installed at temperatures as low as -7°C, and as low as -29°C with optional EternaPrime. No staples or nails required.

COMPOSITION

WindowSeal utilizes EternaBond's advanced MicroSealant™ Technology, a 100% solids formulation of synthetic resins, thermoplastics, and non-curing rubbers, with a built in primer on a stretchable, low density polyethylene (LDPE) backing.

TECHNICAL DATA


Application temperature	66°C to -29°C ambient
Bacteria resistance	Excellent
Flexibility	12.7mm radius at -29°C
Fungal resistance	Excellent
Low temperature flexibility	Excellent
Peel adhesion	135 oz/in width
Sag rating	>93.3°C
Shelf Life	Up to 5 years
Standard case quantity	30.5 sq. meters per case
Temperature flexibility range	-57°C - >93.3°C
Total thickness	20 mils
Water absorption	Less than .05%

SURFACE PREPARATION

Surface must be clean and dry. Moisture, dust, dirt, and other foreign matter should be removed. Remove oil, grease, etc. with a suitable cleaner.

APPLICATION

Install WindowSeal over the repair area, removing the release liner gradually to prevent contamination of the adhesive prior to application. Rub or roll with pressure using your hand or a steel roller to activate bonding process. This material may be applied to clean dry surfaces from 66°C to -29°C ambient. Treat surface with EternaPrime for installations from 5°C to -29°C ambient.



WINDOWSEAL™

Use WindowSeal to seal all windows when installed regardless of surfaces being joined. WindowSeal creates a moisture tight, air tight seal and vapor barrier.

WindowSeal bonds to a wide range of surfaces including: glass, wood, aluminum, vinyl, OSB, polyethylene, polypropylene, polystyrene, Tyvek™, fiberglass, brick, concrete, masonry, and virtually all construction materials.

WINDOWSEAL™

ETERNABOND

featuring  MICROSEALANT® TECHNOLOGY

ETERNABOND-EUROPE
Senlis, France

Phone: 33 (0) 344 99 00 67
www.EternaBond-Europe.com